



BUTTERFLY VALVE(Grooved Type)

Bronze Butterfly Valves, UL Listed / FM Approved Firefly™ Grooved TYPE End Sizes : 2" and 2-1/2"

Factory Installed UL Listed Double Tamper Switch For indoor and Outdoor Use.

Working Pressure 175PSI(12.5Bars)

Max. Test Pressure 350PSI(25.0 Bars)

Max. Working Temp 250°F(120°C)



BUTTERFLY VALVE(Threaded Type)

Bronze Butterfly Valves, UL Listed / FM Approved Firefly™ BT Threaded TYPE End Sizes : 1", 1-1/4", 1-1/2" and 2-1/2"

Factory Installed UL Listed Double Tamper Switch For indoor and Outdoor Use.

Working Pressure 175PSI(12.5Bars)

Max. Test Pressure 350PSI(25.0 Bars)

Max. Working Temp 250°F(120°C)



BUTTERFLY VALVE(Grooved Type)

Grooved Butterfly Valves, UL Listed / FM Approved Firefly™ DG Grooved End Sizes : 2-1/2", 3", 4", 6" and 8"

Factory Installed UL Listed Double Tamper Switch For indoor and Outdoor Use.

Working Pressure 175PSI(12.5Bars)

Max. Test Pressure 350PSI(25.0 Bars)

Max. Working Temp 250°F(120°C)