


REDUCING FITTINGS / Style 16 - 55

STYLE 16




ECCENTRIC REDUCER

Maximum working pressure: 500 psi
For fire protection equipment and approved pressure ratings please contact Modgal.

Nominal Size (Inches / DN)	Pipe Outside Diameter	Coupling Dimensions	Weight Lbs	Approvals
		A		
3" x 2" / 80 x 50	3.500 x 2.375	3.54	1.76	-
4" x 2" / 100 x 50	4.500 x 2.375	4.13	2.98	-
4" x 3" / 100 x 80	4.500 x 3.500	4.02	3.09	-
6" x 3" / 150 x 80	6.625 x 3.500	5.63	7.28	-
6" x 4" / 150 x 100	6.625 x 4.500	5.55	6.17	-

STYLE 55




REDUCING TEE

Maximum working pressure: 500 psi
For fire protection equipment and approved pressure ratings please contact Modgal.

Nominal Size (Inches / DN)	Pipe Outside Diameter	Coupling Dimensions	Weight Lbs	Approvals
		A		
2½" x 1½" / 65 x 40	2,875 x 1,900	2.99	2.65	-
2½" x 2" / 65 x 50	2.875 x 2.375	2.99	2.65	FM / UL*
3" OD x 2"	3,000 x 2,375	2.99	2.65	FM / UL
3" x 2" / 80 x 50	3.500 x 2.375	3.35	3.97	FM / UL*
3" x 3" OD	3,500 x 3,000	3.35	4.19	FM / UL
4" x 2" / 100 x 50	4.500 x 2.375	3.78	6.06	FM / UL*
4" x 3" OD	4,500 x 3,000	3.98	6.62	FM / UL
4" x 3" / 100 x 80	4.500 x 3.500	3.98	6.62	FM / UL*
5" OD x 3 OD	5,500 x 3,000	4.88	10.36	FM / UL
5" OD x 3"	5,500 x 3,500	3.98	10.58	FM / UL
5" OD x 4"	5,500 x 4,500	4.84	11.24	FM / UL
5" x 3 OD	5,563 x 3,000	4.88	10.36	FM / UL
5" x 2½" / 125 x 65	5,563 x 2,875	4.88	10.36	In progress
5" x 3" / 125 x 80	5,563 x 3,500	4.88	10.58	In progress
5" x 4" / 125 x 100	5,563 x 4,500	4.88	11.02	In progress
6" x 2" / 150 x 50	6.625 x 2.375	6.61	24.26	FM / UL
6" x 3" OD	6.625 x 3,000	5.47	15.88	FM / UL
6" x 3" / 150 x 80	6.625 x 3,500	5.47	14.33	FM / UL
6" x 4" / 150 x 100	6.625 x 4,500	5.47	15.44	FM / UL
8" x 3" / 200 x 80	8,625 x 3,500	6.89	28.67	FM / UL
8" x 4" / 200 x 100	8,625 x 4,500	6.89	28.22	FM / UL
8" x 5" OD	8,625 x 5,500	6.89	27.65	FM / UL
8" x 6" / 200 x 150	8,625 x 6,625	6.89	29.11	FM / UL
10" x 6" / 250 x 150	10,750 x 6,625	9.02	65.93	-
10" x 8" / 250 x 200	10,750 x 8,625	9.02	66.15	-
12" x 10" / 300 x 250	12,750 x 10,750	10.00	112.46	-

REDUCING FITTINGS / Style 15

STYLE 15



CONCENTRIC REDUCER

Maximum working pressure: 500 psi
For fire protection equipment and approved pressure ratings please contact Modgal.

Nominal Size (Inches /DN)	Pipe Outside Diameter	Coupling Dimensions	Weight Lbs	Approvals
		A		
1½" x 1¼" / 40 x 32	1,900 x 1,660	2.52	0.58	FM / UL / VDS
2" x 1¼" / 50 x 40	2,375 x 1,660	2.52	0.64	-
2" x 1½" / 50 x 40	2,375 x 1,900	2.52	0.66	FM / UL / VDS
2½" x 1½" / 65 x 40	2,875 x 1,900	2.52	1.10	In progress
2½" x 2" / 65 x 50	2,875 x 2,375	2.52	0.99	In progress
3" OD x 1½"	3,000 x 1,900	2.60	1.10	FM / UL / VDS
3" OD x 2"	3,000 x 2,375	2.56	0.99	FM / UL / VDS
3" x 1¼" / 80 x 40	3,500 x 1,660	2.56	1.21	-
3" x 1½" / 80 x 40	3,500 x 1,900	2.60	0.55	UL
3" x 2" / 80 x 50	3,500 x 2,375	2.60	1.26	FM / UL / VDS
3 x 3" OD	3,500 x 3,000	2.60	1.54	UL / VDS
4" x 2" / 100 x 50	4,500 x 2,375	2.99	1.92	FM / UL / VDS
4" x 3" OD	4,500 x 3,000	2.99	2.05	FM / UL
4" x 3" / 100 x 80	4,500 x 3,500	2.99	2.21	FM / UL / VDS
5" OD x 3" OD	5,500 x 3,000	3.62	3.31	VDS
5" OD x 3"	5,500 x 3,500	3.62	3.53	FM / VDS
5" OD x 4"	5,500 x 4,500	3.62	3.53	FM / VDS
5" x 2½" / 125 x 65	5,563 x 2,875	3.50	3.31	In progress
5" x 3" / 125 x 80	5,563 x 3,500	3.50	3.53	In progress
5" x 4" / 125 x 100	5,563 x 4,500	3.50	3.53	In progress
6" x 2" / 150 x 50	6,625 x 2,375	4.06	5.07	FM / UL / VDS
6" x 3" OD	6,625 x 3,000	4.06	6.17	VDS
6" x 3" / 150 x 80	6,625 x 3,500	4.06	4.41	FM / UL / VDS
6" x 4" / 150 x 100	6,625 x 4,500	4.06	5.95	FM / UL / VDS
6" x 5" OD	6,625 x 5,500	4.06	5.07	FM / VDS
8" x 3" / 200 x 80	8,625 x 3,500	5.04	8.38	FM
8" x 4" / 200 x 100	8,625 x 4,500	5.04	10.58	FM / UL / VDS
8" x 5" OD	8,625 x 5,500	5.04	12.13	FM / VDS
8" x 6" / 200 x 150	8,625 x 6,625	5.04	9.26	FM / UL / VDS
10" x 6" / 250 x 150	10,750 x 8,625	6.06	15.44	-
10" x 8" / 250 x 200	10,750 x 8,625	6.06	19.73	FM / VDS
12" x 10" / 300 x 250	12,750 x 10,750	7.09	30.87	-