


Geberit HDPE bend



Example image



Application purposes

- For building drainage

Characteristics

- Can be welded on both sides with electrofusion coupling

- UV-resistant

Technical data

Product material

PE-HD

Art. no.	DN	d, Ø	arc	X	K
360.045.16.1	40	40 mm	45 °	4 cm	2 cm
361.045.16.1	50	50 mm	45 °	4.5 cm	2 cm
361.088.16.1	50	50 mm	88.5 °	6 cm	2 cm
363.045.16.1	56	56 mm	45 °	4.5 cm	2 cm
363.088.16.1	56	56 mm	88.5 °	6.5 cm	2 cm
364.045.16.1	60	63 mm	45 °	5 cm	2 cm
364.088.16.1	60	63 mm	88.5 °	7 cm	2 cm
365.045.16.1	70	75 mm	45 °	5 cm	2 cm
365.088.16.1	70	75 mm	88.5 °	7.5 cm	2 cm
366.045.16.1	90	90 mm	45 °	5.5 cm	2 cm
366.088.16.1	90	90 mm	88.5 °	8 cm	2 cm
367.045.16.1	100	110 mm	45 °	6 cm	2.5 cm
367.088.16.1	100	110 mm	88.5 °	9.5 cm	2.5 cm
368.045.16.1	125	125 mm	45 °	6.5 cm	2.5 cm
368.088.16.1	125	125 mm	88.5 °	10 cm	2.5 cm
369.045.16.1	150	160 mm	45 °	6.9 cm	2 cm
369.088.16.1	150	160 mm	88.5 °	12 cm	2.5 cm
370.045.16.1	200	200 mm	45 °	18 cm	2.5 cm