


Geberit HDPE expansion socket with double flange



Example image



Application purposes

- For building drainage
- For horizontal and vertical installation

Characteristics

- Double flange for supporting the pipe bracket

- With seal made of EPDM
- UV-resistant

Technical data

Product material

PE-HD

Scope of delivery

- Protective cap

Art. no.	DN	d, ø	D	E	l	H	h	K
379.791.16.1	30	32 mm	4.6 cm	3.5–7 cm	3 cm	12.8 cm	3.9 cm	0 cm
360.700.16.1	40	40 mm	5.5 cm	6.5–13 cm	3 cm	23.7 cm	6.8 cm	3 cm
361.700.16.1	50	50 mm	6.7 cm	6.5–13 cm	3 cm	24 cm	6.8 cm	3 cm
363.700.16.1	56	56 mm	7.4 cm	6.5–13 cm	3 cm	24 cm	6.8 cm	3 cm
364.700.16.1	60	63 mm	8.3 cm	7–13.5 cm	3 cm	24.3 cm	6.8 cm	3 cm
365.700.16.1	70	75 mm	9.7 cm	7–13.5 cm	3 cm	24.6 cm	6.8 cm	3 cm
366.700.16.1	90	90 mm	11.3 cm	7–13.5 cm	3 cm	24.9 cm	6.9 cm	3 cm
367.700.16.1	100	110 mm	13.6 cm	7.5–14 cm	3 cm	25.6 cm	7.3 cm	3.5 cm
368.700.16.1	125	125 mm	15.7 cm	8–14.5 cm	3 cm	26.1 cm	7.4 cm	3.5 cm
369.700.16.1	150	160 mm	19.5 cm	8–14.5 cm	3 cm	26.8 cm	7.4 cm	3.5 cm