



HMER.EX27050 Check Valves

[Page Bottom](#)

Check Valves

[See General Information for Check Valves](#)

SHANDONG LEDE MACHINERY CO LTD

EX27050

No 3998

West Waihuan N Rd

Weicheng District

Weifang, Shandong 261057 CHINA

Swing-type check valve, Model H44X, sizes 2, 2.5, 3, 4, 5, 6, 8, 10, and 12 in., 9 sizes, flange by flange end configuration, with resilient seat size for rated pressure of 300 psig horizontal and vertical positions.

Model H84X, sizes 2, 2.5, 2.5(76.1mm), 3, 4, 5, 5(139.7mm), 6, 6(165.1mm), 8, 10, and 12 in., 12 sizes, groove by groove end configuration, with resilient seat size for rated pressure of 365 psig horizontal and vertical positions.

Model H44X-01, sizes 2, 2.5, 3, 4, 5, 6, 8, 10, and 12 in., 9 sizes, flange by flange end configuration, with resilient seat size for rated pressure of 300 psig horizontal and vertical positions.

[Last Updated](#) on 2016-03-28

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".