Tee & Cross (equal / reducing)



Tee & Cross (equal / reducing)

Category Pipe Fitting
(ANSI B16.9, JIS 2311 SGP, EN10)

Product Details:

Place of Origin: **CHINA**

Brand Name:	**XINFENG**
Certification:	**ISO, CE**
Standard:	**ANSI B16.9 ANSI B16.28 DIN2605/ 2615/ 2616/ 2617 JIS B2311 GOST 17375/ 17376/ 17377/ 17378.**
Type:	**45D/90D/180D ELBOW LR/SR, EQUAL TEE, REDUCING TEE,CONCENTRIC REDUCER, ECCENTRIC REDUCER, CAP, CROSS, SADDLE.**
Size:	**1/2" - 48"**
Wall Thickness:	**SCH10, SCH20, SCH30, STD, SCH40, SCH60, XS, SCH80, SCH100, SCH120, SCH140, SCH160, XXS, JIS, DIN**
Connect Type:	**Butt Welded**
Surface Treatment:	**Black paint, light oil, hot dip Galvanized.**
Material:	**Carbon steel: ASTM A234 WPB / 20#/ P265GH/ST37.2; Stainless steel: 304/304L, 316/316L**


Payment & Shipping Terms:

Minimum Order Quantity:	**1TONS**
Packaging Details:	**PLYWOOD CASES AND PALLETS**
Payment Terms:	**L/C, D/P, T/T**
Delivery Time:	**10-45DAYS**
Supply Ability:	**5000TONS/MONTH**

Product Inquiry

Related Products

Technical Drawings



Standard drawing of Straig

The straight tee is a three-way fitting used to make perpendicular c

Leave Messages

Please enter your E-mail

submit

resemblance to the letter T. The straight cross is a four-way fitting u
pipe. It resembles a crossroad. Lines that connect to the main run c
often called the “header”. The word “straight” denotes that all three(for tee) or four(for cross) outlets are the same pipe size.

Dimensions

NPS	O.D mm inch	C mm inch	M mm inch
1/2	21.3 0.84	25 1.00	25 1.00
3/4	26.7 1.05	29 1.12	29 1.12
1	33.4 1.32	38 1.50	38 1.50
1-1/4	42.2 1.66	48 1.88	48 1.88
1-1/2	48.3 1.90	57 2.25	57 2.25
2	60.3 2.38	64 2.50	64 2.50
2-1/2	73.0 2.88	76 3.00	76 3.00
3	88.9 3.50	86 3.38	86 3.38
3-1/2	101.6 4.00	95 3.75	95 3.75
4	114.3	105	105

	4.50	4.12	4.12
5	141.3 5.56	124 4.88	124 4.88
6	168.3 6.62	143 5.62	143 5.62
8	219.1 8.62	178 7.00	178 7.00
10	273.0 10.75	216 8.50	216 8.50
12	323.8 12.75	254 10.00	254 10.00
14	355.6 14.00	279 11.00	279 11.00
16	406.4 16.00	305 12.00	305 12.00
18	457.0 18.00	343 13.50	343 13.50
20	508.0 20.00	381 15.00	381 15.00
22	559.0 22.00	419 16.50	419 16.50
24	610.0 24.00	432 17.00	432 17.00
26	660.0 26.00	495 19.50	495 19.50
28	711.0 28.00	521 20.50	521 20.50

30	762.0 30.00	559 22.00	559 22.00
32	813.0 32.00	597 23.50	597 23.50
34	864.0 34.00	635 25.00	635 25.00
36	914.0 36.00	673 26.50	673 26.50
38	965.0 38.00	711 28.00	711 28.00
40	1016.0 40.00	749 29.50	749 29.50
42	1067.0 42.00	762 30.00	711 28.00
44	1118.0 44.00	813 32.00	762 30.00
46	1168.0 46.00	851 33.50	800 31.50
48	1219.0 48.00	889 35.00	838 33.00

*NPS: Nominal Pipe Size; O.D: Outside Diameter at Bevel; C: Center-to-End, Run; M: Center-to-End, Outlet.

Package